Dibley 9937



Upholstery **Dibley** 9937

Specifications

Content

100% recycled polyester

Weight

 11.2 ± 0.5 oz./lin. yd.

Width

54" min. useable

Repeat

1.1875" vertical, 1.5" horizontal

Backing

SBR backcoating

Treatment

BLOCKaide®

Miscellaneous

Every effort has been made to ensure color accuracy of the digital images, however, please order a sample before specification. Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric. Pattern shown railroaded.

Proudly woven in the USA supporting our local communities.

Visit guilfordofmaine.com for samples.

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Performance



Colorfastness to Light (AATCC 16 Option 3)

Grade 4 min. at 40 hours



Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet



Breaking Strength (ASTM D5034)
150 lbf min. warp and fill

Seam Slippage (ASTM D4034) 60 lbf min. warp and fill

Pilling Resistance (ASTM D3511) Class 4 min.



Flammability

CA Technical Bulletin 117-2013 Section 1 NFPA 260/UFAC Fabric Classification - Class I



Abrasion (ASTM D4157)

50,000 double rubs min. cotton duck

*ACT® registered certification marks.

Guilford of Maine

guilfordofmaine.com